

## PRODUCT SPECIFICATION SHEET multithene 1063

PE HD Compound

### multithene 1063

#### Description

PE HD-Compound

#### Properties

Application	extrusion, injection moulding
Shape	lenses
Filtration	80 µm
Colour	black, grey

#### Packing

Big Bag on non-returnable pallet  
H x W x D: ca. 1.85 m x 1.06 m x 1.06 m  
weight app. 1,000 kg per Big Bag  
Silo on request

#### Purity

Melt flow index MFR at 190°C/5kg (DIN ISO 1133)	1.5-2.1 g/10 min
Density	≥ 0.945 g/cm <sup>3</sup>
Bulk density	≥ 480 kg/m <sup>3</sup>
Surface humidity	≤ 0.06 %

Our products are manufactured with the utmost care and are subject to regular quality controls. Nevertheless, slight material variations can occur.

All data stated on our product information are average values and are based on our current knowledge and experience according to DIN EN 15 344.

They do not release the user from careful examination when applying and using our products, due to the variety of possible influences.

Legally binding commitments of certain properties for precise applications cannot be made from our stipulations. Any property rights as well as existing laws and regulations are to be observed by the receiver respectively processor of our products, on individual responsibility.

Our products are not suitable for the application in the context of the act (EC) no. 282/2008. In the following, our general conditions of sale are valid.

issue: 14.12.2016

